

# WHEEL LEVELING SET

BY **Weigh Safe!**  
TRAILER HITCHES

## INSTRUCTIONS

### STEP 1

Set Rubber Mat & Wheel Leveler under the tire as shown. Push Wheel Leveler as far as it can go.



### STEP 2

Slowly drive onto Wheel Leveler until vehicle is level.



### STEP 3

Wedge smaller Wheel Chock under Wheel Leveler as shown.



### STEP 4

Put vehicle in neutral to let the wheel settle.



### NOTE:

For dual axle trailers with limited space (less than 2") between tires, a maximum of 4" can be cut off the end of the Wheel Leveler.



**INSTRUCTIONAL  
VIDEO**





# WARNING



## IMPROPER USE MAY RESULT IN SERIOUS INJURY OR DEATH

FAILURE TO FOLLOW THESE WARNINGS COULD CAUSE UNSTABLE CONDITIONS. IMPROPER USE MAY RESULT IN PROPERTY DAMAGE, INJURY OR DEATH.

- **ALWAYS** inspect each component for damage prior to use. **DO NOT** use if damaged.
- **ALWAYS** align Wheel Levelers with centerline of tires. Failure to do so can lead to instability.
- **ALWAYS** put the vehicle in park and engage the parking brake.
- **ALWAYS** keep hands, feet and other objects clear during leveling process.
- **ALWAYS** ensure components are dry to prevent slipping during leveling.
- **NEVER** stack additional items on top of or below of Wheel Leveling components for additional height.
- **NEVER** exceed weight rating capacity.
- **ONLY** use the Wheel Leveling Set for it's intended use.



### QUESTIONS OR CONCERNS?

Contact our Customer Support team!

Call or text us at 801.820.7020

Email us at [customersupport@weigh-safe.com](mailto:customersupport@weigh-safe.com)