



# Weigh Safe!

MEASURES TONGUE WEIGHT

## Instructions



**STEP 1:** Ensure that the Ball Retaining Pin is inserted fully into the Weigh Safe slider. **Do not operate without ball pin in place.**



**STEP 2:** Place the Weigh Safe slider at the desired drop on the Drawbar in order to ensure that your vehicle and trailer are properly positioned.



**STEP 3:** Insert the Keylock Assembly (WS03) into the Weigh Safe Slider when you have achieved the desired position along the Drawbar and lock in place by turning



**STEP 4:** Pull on the Keylock Assembly (WS03) to ensure that it has been engaged. **Do not operate without making sure Keylock Assembly is securely locked in place.**

## \*\*\*IMPORTANT SAFETY INFORMATION\*\*\*

Ensure safety chains are attached between vehicle and trailer. DO NOT attach chains directly to hitch. Never exceed the LOWER rating between: A) Towing vehicle manufacturer's load OR B) Weigh Safe Hitch GTW hitch ratings: 7,500 lbs. (1-7/8" ball), 8,000 lbs. (2" ball), 10,000 lbs. (2-5/16" ball & 2" shank), 14,500 lbs. (2-5/16" ball & 2.5" shank), 21,000 lbs. (2-5/16" ball and 3" shank)/ Tongue Weight should be between 10-15 % of gross trailer weight. Weigh Safe Hitch max GTW is 1,500 lbs. (2" shank) and 2,200 lbs. (2.5" & 3" shanks). Secure your 180 Hitch to standard 2", 2.5" or 3" receiver with locking pin.